

PRORAČUN HORIZONTALNE RASVIJETLJENOSTI T E P - ZAGREB

REKONSTRUKCIJA JR CARDUCCI

ULAZNI PODACI DUŽ.RASTERA 17.0 M
 ŠIR.RASTERA 5.5 M

RASPORED SVJETILJAKA Dvoredno,cik-cak,h=4m

REZULTATI PRORAČUNA

HORIZONTALNA RASVIJETLJENOST /LX/

X/M/ Y/M/	.00	2.13	4.25	6.38	8.50	10.63	12.75	14.88	17.00
.00	44.6	37.8	24.2	15.7	13.9	17.2	25.8	38.2	43.8
.92	39.6	32.8	21.8	15.8	15.1	18.4	24.5	33.4	38.0
1.83	34.7	28.7	20.1	16.4	17.1	20.3	24.4	29.5	32.0
2.75	31.9	25.8	19.5	17.5	19.9	24.0	26.0	26.9	27.6
3.67	33.0	25.1	19.4	19.0	24.3	29.8	29.9	26.5	25.4
4.58	36.1	26.0	20.0	21.1	29.7	36.7	34.8	28.0	25.2
5.50	40.6	28.1	20.9	23.7	35.2	43.3	40.3	30.7	25.6

ESR 26.0
 EMIN 13.9 X 8.50 Y .00
 EMAX 44.6 X .00 Y .00

EMIN/ESR .5363
 EMIN/EMAX .3122

SVJETILJKE U PRORAČUNU

N	X-KOORD	Y-KOORD	H	KUT Y	DELTA	TIP	FI	IZVOR SVJETLOSTI
1	-18.00	-2.50	4.00	.00	.00	S11	11.6	NaVt 2x70W
2	.00	-2.50	4.00	.00	.00	S11	11.6	NaVt 2x70W
3	17.00	-2.50	4.00	.00	.00	S11	11.6	NaVt 2x70W
4	33.00	-2.50	4.00	.00	.00	S11	11.6	NaVt 2x70W
5	51.00	-2.50	4.00	.00	.00	S11	11.6	NaVt 2x70W
6	-14.00	8.00	4.00	.00	.00	S11	11.6	NaVt 2x70W
7	-2.00	8.00	4.00	.00	.00	S11	11.6	NaVt 2x70W
8	11.00	8.00	4.00	.00	.00	S11	11.6	NaVt 2x70W
9	23.00	8.00	4.00	.00	.00	S11	11.6	NaVt 2x70W
10	40.00	8.00	4.00	.00	.00	S11	11.6	NaVt 2x70W
11	52.00	8.00	4.00	.00	.00	S11	11.6	NaVt 2x70W

POPIS TIPOVA SVJETILJKI

TIP: S11 OPIS TIPa: Rovinjski ribarski feral-optika kao KN 163, KN 133